

Compact Fluorescent Energy Saver Circlines

Ideal for use in table lamps, floor lamps and ceiling fixtures

**ENERGY SAVER** 

# Energy saver circlines

Philips Compact Fluorescent Energy Saving Circlines provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

#### **Direct replacement for incandescent bulbs**

- Instant on
- · Adjustable lamp height

## Superior lighting quality

- Offers incandescent-like light distribution over a wide surface
- · Provides warm and inviting soft white light

## Long life

· Lasts 9 years\*

#### **Energy savings**

Saves up to \$110 over the life of the lamp when you replace a 150W incandescent lamp with a 40W energy saver circline\*\*

<sup>\*\*</sup> Energy savings based on wattage saved x replacement lamp rated average life (10,000 hours) ÷ 1000 x \$0.10 kWh rate.



<sup>\*</sup> Based on an average daily usage of 3-4 hours per day, 7 days per week.

## Compact Fluorescent Energy Saver Circlines

## Ordering, Electrical and Technical Data

Product	Description	Volts	Nom. Watts	Approx. Incand. Equiv.	Base	Color Temp. (Kelvin)	CRI	Approx. Initial Lumens <sup>1</sup>	Outer Diam.	Rated Avg. Life (Hrs.) <sup>2</sup>	Min. Starting Temp.	Max. Ambient Temp.
15719-8	Two Piece Circline 32W	120	32	135W	Med.	2700	82	2200	5.5	10,000	-22°F/-30°C	
15720-6	Two Piece Circline 40W	120	40	150W	Med.	2700	82	2650	7.3	10,000	-22°F/-30°C	140°F/60°C

## **Shipping Data**

	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)		Case Weight (lbs.)					SKU Dimensions (W x D x H)(In.)		Pallet Dimensions (W x D x H)(ln.)
15719-8	15719-7	15719-2	4	2.85	0.578	208	52	4	$4.3 \times 6.8 \times 6.9$	$7.2 \times 18.4 \times 7.6$	36.8 x 47.1 x 30.3
15720-6	15720-3	15720-8	4	3.0	0.827	160	40	4	4.6 x 8.4 x 8.1	$8.4 \times 18.8 \times 9.0$	$37.6 \times 42.2 \times 36.0$

■ ENERGY STAR® Bulb: As an ENERGY STAR® Partner, Philips has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. Above specifications subject to change without notice.

WARNINGS & CAUTIONS: Do not use with dimmers. Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Turn off power before changing bulb. Outdoor use requires a weather protected fixture. This device complies with Part 18 of the FCC Rules.

Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Reliable operating temperature range -22F/-30C to 140F/60C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

	<b>A</b>		Q <sub>f</sub>			<b>₽</b>			2000	
Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan
Decorative Twister	•		•		•			•		
Universal	•	•	•	•	•	•	•	•		
3-Way	•									
Reflector Flood							•	•		
Dimmable Reflector Flood							•	•		
Candle		•	•		•					•
Vanity & Decor Globe								•	•	•
Soft White Plus	•	•	•		•	•		•		•
Outdoor		•				•				
Bug-A-Way		•								
Circline	•									
Genie	•	•	•	•	•	•	•	•	•	•



Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.
Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours.
Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.